



GROUND FLOOR PLAN SHOWING 1ST. FLOOR SUPERSTRUCTURE OVER
LINTELS SHOWN ARE OVER GROUND FLOOR OPENINGS

DO NOT SCALE		COPYRIGHT RESERVED	
GENERAL NOTES			
1. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH THE ARCHITECTS, SPECIALISTS AND ENGINEERS DRAWINGS AND SPECIFICATIONS. ANY DISCREPANCIES ARE TO BE REPORTED TO THE ARCHITECT/ENGINEER IMMEDIATELY.			
2. MATERIALS AND CONSTRUCTION TO BE IN ACCORDANCE WITH ALL THE BRITISH STANDARDS AND CODES OF PRACTICE.			
3. CATNIC LINTELS TO BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURERS INSTRUCTIONS.			
4. ALL TRUSSES AND RAFTERS TO BE STRAPPED TO WALLS IN ACCORDANCE WITH THE BUILDING REGULATIONS.			
5. FLOOR JOISTS TO BE TIED TO WALLS IN ACCORDANCE WITH THE BUILDING REGULATIONS.			
6. EXTERNAL CAVITY WALLS TO HAVE BF30 MASONRY REINFORCEMENT INSTALLED AT 450 Crs. VERTICALLY			
7. EJ DENOTES EXPANSION JOINTS IN MASONRY.			